



## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>7</sup> : <b>H04Q 7/32, H04L 9/32</b>		A1	(11) International Publication Number: <b>WO 00/36860</b>
			(43) International Publication Date: 22 June 2000 (22.06.00)


  

<p>(21) International Application Number: PCT/FI99/01010</p> <p>(22) International Filing Date: 7 December 1999 (07.12.99)</p> <p>(30) Priority Data: 982727 16 December 1998 (16.12.98) FI 990757 6 April 1999 (06.04.99) FI</p> <p>(71) Applicant (for all designated States except US): NOKIA NETWORKS OY [FI/FI]; Keilalahdentie 4, FIN-02150 Espoo (FI).</p> <p>(72) Inventors; and</p> <p>(75) Inventors/Applicants (for US only): EINOLA, Heikki [FI/FI]; Kaksoiskiventie 7-9 B 5, FIN-02760 Espoo (FI). RA-JANIEMI, Jaakko [FI/FI]; Lapinrinne 2 A 11, FIN-00180 Helsinki (FI). HULKKONEN, Tony [FI/FI]; Porvoonkatu 1 F 214, FIN-00510 Helsinki (FI). BÄCK, Juha [FI/FI]; Kuloosaaren puistotie 44 B 22, FIN-00570 Helsinki (FI).</p> <p>(74) Agent: JOHANSSON, Folke; Nokia Corporation, P.O. Box 319, FIN-00045 Nokia Group (FI).</p>	<p>(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).</p> <p><b>Published</b> With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</p>
--	--

(54) Title: A METHOD FOR CONTROLLING CONNECTIONS TO A MOBILE STATION

## (57) Abstract

The present invention is a novel and improved method for managing in a single location the ciphering keys and algorithms used for encrypting or ciphering the communications of a specific mobile station with multiple core networks or core network entities. Further another aspect of the invention is that the management location is movable as the mobile station moves within the radio access network.



**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakistan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

## **A method for controlling connections to a mobile station**

### **TECHNICAL FIELD OF THE INVENTION**

5 The present invention relates to communication networks capable of ciphering and deciphering and especially to a method for managing keys in such communication networks.

### **BACKGROUND OF THE INVENTION**

10

Radio transmission is by nature more prone to eavesdropping and fraud than fixed wire transmission. Listening to communications is easy and does not require access to special locations. The GSM cellular system has alleviated this problem by introducing authentication and encryption or ciphering. Next  
15 the GSM authentication and ciphering procedures are explained shortly in reference with Figure 1. More details can be found for example in Mouly et. al.: "The GSM system for mobile communications".

Figure 1 illustrates current GSM system incorporated with a general packet  
20 radio or GPRS network. The complete network comprises three different functional sub-networks, a Radio Access Network, a Circuit Switched or first core network, and a Packet Switched or second core network. The Radio access network comprises Base Station Controllers or BSC's 30 (only one is shown) and Base Stations or BS's 20. The first core network comprises  
25 Mobile Switching Centers with Visitor Location Register or MSC/VLR 40 and Home Location Register with Authentication Center or HLR/AuC 50. The first core network comprises additional MSC/VLR's and HLR/AuC's, which are not shown for the sake of simplicity. The second core network comprises Serving General packet Service Node or SGSN 60. The second  
30 core network comprises additional General packet Service Nodes or GSN's,

which are not shown for the sake of simplicity. The both core networks may share a common Home Location Register with Authentication Center or HLR/AuC 50.

- 5 When a User Equipment UE (or Mobile Station MS) 10 accesses the first core network it registers itself in the MSC/VLR 40. After receiving a registration request or a service request from the mobile, MSC/VLR 40 transmits to HLR/AuC a request including IMSI to acquire authentication triplets consisting of RAND, SRES and Kc1. In GSM the MM or the mobility  
10 management protocol implements the functionality for the authentication. The triplets are of a predetermined length and calculated by using a secret key Ki, known only to the authentication center and the SIM card in the mobile. After receiving the triplets from HLR/AuC, the MSC/VLR sends the challenge, RAND, to the MS in an authentication request to authenticate that  
15 particular MS. As part of the succesful registration, the MSC/VLR updates the location of the MS to HLR and downloads the subscriber data from HLR.

- The mobile 10 has the secret key Ki in it's SIM card. The secret key Ki is stored on subscription by the operator and is not visible for the users of the  
20 mobile or for any other party for that matter. It is identical to the secret key Ki stored in the Authentication Center 50. The secret key Ki is applied together with the random number RAND into a predetermined algorithm called A3 to produce a signed response SRES. The mobile 10 then transmits a message containing SRES to the MSC/VLR 40, which compares it with the SRES  
25 received from the AuC 50. If the comparison is succesful, the mobile 10 is authenticated and allowed to access the network. At the same time with calculating the SRES, the mobile applies RAND and Ki to another predetermined algorithm called A8 to produce the ciphering key Kc1. If the authentication was succesful and the network should so decide, all subsequent  
30 transmissions with the mobile 10 over the air interface are ciphered.

For this the MSC/VLR transmits the ciphering key Kc1 to the BSC which is in communication with the mobile 10, and the BSC subsequently delivers the Kc1 further to the BTS communicating with the MS and the ciphering or encryption takes place in the base station and the mobile according to yet another predetermined algorithm, for example A5. Once MSC/VLR has decided that ciphering will be used, the BSC makes a decision up on the actual algorithm. In GSM there are currently two ciphering algorithms to select from.

10

If the mobile wants to access the second core network it registers itself in the SGSN 60. The procedure for authentication is similar to the procedure with the first core network, with the exception that the ciphering key Kc2 is not transmitted to the base station (BSS part of the system) currently in communication with the mobile 10. In other words, the ciphering takes place in SGSN and in MS. The SGSN 60 retains the ciphering key Kc2 within itself and performs the ciphering.

15

Thus, the prior art system uses different ciphering keys for ciphering the communications with two different core networks and the ciphering is applied to two different radio connections as the radio channels used for communicating with MSC and SGSN are distinct. As a result, a GSM MS having simultaneous communications with both MSC and SGSN utilizes two ciphering keys on two different radio channels or connections having both their own independent control in the network.

20

25

The fact that the ciphering and the control of the ciphering takes place at different locations, may cause consistency problems. The fact that radio access network is not able to access the signalling messages of the second core network at all, may turn out to be problematic in future networks, when

30

all radio resources used by a specific user should be managed in conjunction in a system having two CN nodes controlling the ciphering. In this case, the radio resources reserved for simultaneous connections to MSC and SGSN should be managed by a single entity in the radio access network part of the system, but still there would be two entities controlling the ciphering.

It is proposed that in UMTS there will be only one RRC or radio resource control protocol, controlling both the connection to the MSC and to the SGSN. If only one key is used at a time for both connections, the problem is, how to communicate to the other CN node that its key is not going to be used. Yet another problem, relates to handovers controlled by a CN entity.

It is therefore an object of the present invention to efficiently manage the ciphering keys and algorithms for ciphering and deciphering user data communicated between different core networks and a mobile station.

It is another object of the present invention to efficiently manage the ciphering keys and algorithms for ciphering and deciphering signalling data communicated between different core networks and a mobile station.

It is still another object of the present invention to efficiently transfer the ciphering parameters when the serving radio network controller is handed over to another radio network controller, which then becomes a new serving radio network controller.

## SUMMARY OF THE INVENTION

The present invention is a novel and improved method for managing in a single location the ciphering keys and algorithms used for encrypting or ciphering the communications of a specific mobile station with multiple core

networks or core network entities. Further another aspect of the invention is that the management location is movable as the mobile station moves within the radio access network.

5 The preferred embodiment of the present invention relates to a 3<sup>rd</sup> generation mobile network, for which abbreviations UMTS or WCDMA are used. The network is shown in Fig. 2. The network comprises multiple subnetworks. The radio access network or UTRAN (UMTS Terrestrial Radio Access Network) comprises multiple Radio Network Controllers or RNC's 130 each  
10 of which controls multiple Base Stations or BS's 120. The first core network comprises a Mobile Switching Center with Visitor Location Register or MSC/VLR 140 and a Home Location Register with an Authentication Center or HLR/AuC 150. The first core network comprises additional MSC/VLR's and HLR/AuC's, which are not shown for the sake of simplicity. The second  
15 core network is a packet network and comprises Serving General packet Service Node or SGSN 160. The second core network comprises additional Gateway GPRS Support Nodes or GGSN's, which are not shown for the sake of simplicity. Note that the UTRAN may be connected to another operators core network or a third core network similar to the first core network.

20

Since the air interface access method is CDMA, the mobile 110 is capable of communicating with multiple base stations at the same time (called soft or diversity handover). When that occurs, all transmissions from the mobile 110 are directed to one RNC, called serving RNC or SRNC, in which the  
25 transmissions are combined into one transmission for further sending towards the intended core network. Also, the SRNC has the control over the radio connections.

In the preferred embodiment a mobile station establishes communication with  
30 one core network or core network entity or vice versa. In the establishment

the network requests mobile to authenticate itself as explained above. At the same time with the authentication the mobile and the network (or CN node) calculate identical ciphering keys Kc1. In the preferred embodiment of the invention the core network or core network entity, which calculated the ciphering key does not start ciphering user data or signalling messages but generates and transmits a message comprising the key and data indicative of the algorithm to be used to a ciphering controller 180, which is preferably located in the serving radio network controller. The ciphering controller receives said message and starts ciphering the data and signalling messages flowing from the core network towards to mobile station and to decipher the data and signalling messages flowing from the mobile to the core network.

In the preferred embodiment of the invention another core network or network entity may establish communication with the mobile station or vice versa while the communication with the first core network is still active. The second core network or network entity authenticates the mobile and second ciphering keys Kc2 are calculated. Then, as described above, the second core network generates and transmits a second message comprising the second key and data indicative of the algorithm to be used with the second key to the ciphering controller. The ciphering controller receives said second message and compares the first and second ciphering keys and the related algorithms. If the first and second ciphering keys and the related algorithms are equally reliable, the ciphering controller ciphers and deciphers data and signalling messages to and from the first and second core networks with the key and algorithm it was using already. This is illustrated in figure 3. However, if the second ciphering key and it's related algorithm provide improved encryption or it is desirable not to use the same key any more (even if the quality or strength of the ciphering were the same) the ciphering controller starts using the second key and it's related algorithm for the communication with the first core network as well. This is illustrated in figure 4. The scenario presented in



figure 3 may result in that the same key is used for a very long time, as the activity may be chained between MSC and SGSN. The need or desire to change the key will result in that ciphering control will generate and transmit MS a message commanding it to act accordingly.

5

In another embodiment of the present invention the respective different keys are used for ciphering user data in different communications but the key and it's related algorithm with higher ciphering capabilities are used for ciphering the signalling messages to and from both core networks.

10

In yet another embodiment, after receiveing the message containing the second ciphering key Kc2, the ciphering control acknowledges said message with another message containing information indicative of the selected ciphering key and algorithm. The communication of the key in use into the second CN node (possessing Kc2) may also take place in the reception of initial message as part of the COMPLETE LAYER 3 INFO message. By doing so, the second CN will become aware immediately that the radio connection for signalling is already ciphered and as a result there would be no need to commend ciphering on.

20

In another embodiment, there is only one entity controlling the ciphering in CN. This approach is illustrated in figure 6. In this case there is no need for managing of the keys in RNC as described above. As a result, the situation is from the RNC point of view the same as in the prior art system GSM.

25

However, in the CN side the situation is new, as a single entity is managing both the services (and protocols) offered by the MSC and SGSN. In such a configuration, the system is characterized with that the ciphering belonging to connections or services belonging inherently to MSC and SGSN in GSM are managed by the said single CN entity, which is using a single signalling flow between the radio access network and core network, i.e., over Iu-interface.

30

In another embodiment there is an interface between the two ciphering control entities in CN providing the required coordination. In practice, there could be an interface called Gs between the MSC and SGSN. The Gs as such is present in the prior art GSM system, but it does not contain functionality to coordinate the ciphering keys. Figure 7 illustrates one implementation or realization of the coordination provided by the enhanced Gs interface. The activity enquiry response may contain also other data such as SRNC ID to avoid paging in MT case in non-serving RNCs, but belonging to LA/RA the terminal in currently registered in.

In the preferred embodiment of the present invention it is possible that the communications to the mobile station are rerouted via another serving radio network controller. Should this occur, the parameters used for ciphering and deciphering (along with other parameters required to establish the communication via the target controller) need to be transferred to the new location of the ciphering controller via CN. This is done by signalling the parameters or info on them transparently through the corresponding core networks. Alternatively this may be done by signalling the parameters over Iu interface between radio network controllers.

#### BRIEF DESCRIPTION OF THE DRAWINGS

The invention is described in more detail in the following with reference to the accompanying drawings, of which

Figure 1 is an illustration of prior art mobile communication system.

Figure 2 is an illustration of the UMTS network of the preferred embodiment of the present invention.

Figure 3 illustrates the selection of one ciphering key for all communication.

5 Figure 4 illustrates the case when ciphering key is changed during the communication.

Figure 5 illustrates the signalling sequence in SRNC relocation.

10 Figure 6 illustrates the case having only one core network ciphering entity.

Figure 7 illustrates the activity enquiry from first core network entity to second core network entity.

15

Figure 8 illustrates an alternative signalling sequence in SRNC relocation.

Same reference numerals are used for similar entities in the figures.

20

#### DETAILED DESCRIPTION

The ciphering is likely to be done within UTRAN in UMTS. In the two MM option there are two entities, i.e., MSC and SGSN, which may request  
25 ciphering in the radio interface.

It is assumed that in UMTS the ciphering key and the allowed ciphering algorithms are supplied by CN domains to the UTRAN usually in the beginning of the connection. Receipt of the ciphering command message at  
30 the UTRAN will cause the generation of a radio interface ciphering command

message and, if applicable, invoke the encryption device and start data stream ciphering. The CN domain is noted if the ciphering is executed successfully in the radio interface and the selected ciphering algorithm.

- 5 When new connection is established from other CN domain, which is not having any connection to the UE, the new CN domain also supplies the ciphering key and the ciphering algorithms allowed to use to UTRAN in the beginning of the connection. This is due to the fact CN domains are independent from each other, in the sense of ciphering.

10

If it is assumed that only one ciphering key and one ciphering algorithm are used for all connections, this leads to a situation, in which there are (two) more than one ciphering keys supplied from CN domains and only one of them is used.

15

To handle this situation, UTRAN must select either one of the ciphering keys. If there are no differences between the ciphering requirements requested by two CN domains or there is no desire to change the key then, e.g., the first ciphering key and the algorithm is maintained as shown in Figure 3.

20

As a result of the selection of the ciphering key between two different CN domains (if both CN domains have active connection(s) to the UE) either one of the CN domains does not know the correct ciphering key used for the connection(s). Only UTRAN and UE know the correct ciphering key used.

25

It may be required to use one ciphering key for, e.g., one radio access bearer. Different user plane bearers are ciphered by different ciphering keys supplied by the single CN domain respectively. This means that, e.g., for two calls via MSC, two keys would be used for the data streams. However, in the control

30

plane only one ciphering key is used and therefore in the control plane there

must be coordinated between ciphering keys supplied by CN domains or domain.

5 The coordination in the control plane is similar to what is presented for one ciphering key used in UTRAN. In the control plane, UTRAN must select either one of the ciphering keys supplied from CN domains if both CN domains are active or from a CN domain in case more than one bearers were in use.

10 In GSM, when inter-BSC handover is performed, MSC sends the ciphering key and allowed algorithms to the target BSC in the BSSMAP HANDOVER REQUEST message. In GPRS, because the SGSN performs the ciphering, the inter-BSC handover does not cause any need for the ciphering key management.

15 For UMTS, the GSM approach is not applicable on the serving RNC (SRNC) relocation, because CN domains do not necessarily know the correct ciphering key used as it is described above. The solution is to relay info on ciphering transparently via the CN in SRNC relocation.

20 Figure 4 describes the ciphering key signalling in an inter-RNC handover. The ciphering key is transferred in the transparent (to CN) UTRAN information field from the source RNC to the target RNC in the RANAP SRNC REQUIRED and RANAP SRNC REQUEST messages. In this way the  
25 correct ciphering key is transferred to the target RNC.

In the handover from UMTS to GSM, the ciphering key cannot be transferred transparently like it is proposed for UMTS. The CN (or IWU) has to build the BSSMAP HO REQUEST message, having the ciphering key from the MSC.

2G-SGSN receives its ciphering key from the old 3G-SGSN via Gn-interface as it is done in GPRS.

5 If the ciphering keys used in UMTS are different compared to GSM, e.g., the ciphering key length is different, both MSC and SGSN ciphering keys must be changed in UMTS-GSM handover.

10 In GSM, the A-interface BSSMAP supports a transparent field in the BSSMAP HO REQUIRED and HO REQUEST messages, which allows to utilize the proposed solution also GSM CN-connected to the UTRAN.

15 An alternative signalling is presented in figure 8. In this case the keys are managed like in MSC in GSM (described above), but the transparent info contains indication on, which key is actually in use. For example, in case the key supplied by SGSN was in use in source, the target would receive two keys together with an indication that the SGSN key is in use. The advantage of this alternative is the similarity with GSM, which makes handover with GSM more easy with GSM as the principle on key management in CN (actually only MSC) is the same in both GSM and UMTS.

20

In view of the foregoing description it will be evident to a person skilled in the art that various modifications may be made within the scope of the invention. While a preferred embodiment of the invention has been described in detail, it should be apparent that many modifications and variations thereto  
25 are possible, all of which fall within the true spirit and scope of the invention.

Claims


1. A communication network comprising a user equipment, an access  
network and a plurality of core networks, wherein said user equipment is  
5 capable of being simultaneously in communication with at least two of  
said plurality of core networks, **characterized in** that said at least two of  
said core networks each comprise means for communicating separate  
ciphering parameters to said access network; and said access network  
comprises means for selecting one of said separate ciphering parameters  
10 for ciphering the communications between said user equipment and said at  
least two of said plurality of core networks.
2. A communication network according to claim 1, **characterized in** that  
said access network further comprises means for ciphering said  
communications between said user equipment and said at least two of said  
15 plurality of core networks with said selected one of said separate ciphering  
parameters.
3. A communication network according to claim 1 or 2, **characterized in**  
that said ciphering parameter is a ciphering key or a ciphering algorithm  
or a combination of both.
- 20 4. A method of ciphering in a communication network comprising a user  
equipment, an access network and a plurality of core networks, wherein  
said user equipment is capable of being simultaneously in communication  
with at least two of said plurality of core networks, **characterized in** that  
said at least two of said core networks each communicate separate  
25 ciphering parameters to said access network; and that said access network  
selects one of said separate ciphering parameters for ciphering the  
communications between said user equipment and said at least two of said  
plurality of core networks.
5. A method of ciphering according to claim 4, **characterized in** that said  
30 access network further ciphers said communications between said user

equipment and said at least two of said plurality of core networks with said selected one of said separate ciphering parameters.

- 5      6. A method of ciphering according to claim 4 or 5, **characterized in** that said ciphering parameter is a ciphering key or a ciphering algorithm or a combination of both.
- 10      7. A method of ciphering according to claim 4, **characterized in** that said access network comprises a plurality of entities dedicated for managing the ciphering of communications with user equipments located in a geographical area allocated to said respective entities, and that when said user equipment moves from a geographical area allocated to a first ciphering managing entity to a geographical area allocated to a second ciphering managing entity, said first ciphering managing entity communicates used ciphering parameters to said second ciphering managing entity by signalling over said at least two of said plurality of
- 15      core networks.
- 20      8. An access network element connected to a plurality of core networks, and to a user equipment, wherein said user equipment is capable of being simultaneously in communication with at least two of said plurality of core networks over said access network, **characterized in** that said access network comprises means for receiving separate ciphering parameters from said core networks; and said access network comprises means for selecting one of said separate ciphering parameters for ciphering the communications between said user equipment and said at least two of said plurality of core networks.



1 / 6

FIGURE 1






FIGURE 2



3 / 6

FIGURE 3



4 / 6

FIGURE 5

5 / 6

FIGURE 4FIGURE 6

6 / 6

FIGURE 7FIGURE 8

# INTERNATIONAL SEARCH REPORT

International application No.

PCT/FI 99/01010

## A. CLASSIFICATION OF SUBJECT MATTER

IPC7: H04Q 7/32, H04L 9/32  
According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC7: H04Q, H04L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0779760 A1 (NOKIA MOBILE PHONES LTD.), 18 June 1997 (18.06.97), see the whole document --	1-8
A	WO 9715161 A1 (NOKIA TELECOMMUNICATIONS OY), 24 April 1997 (24.04.97), see the whole document --	1-8
P,A	EP 0957651 A2 (SECTRA COMMUNICATIONS AB), 17 November 1999 (17.11.99), see the whole document --	1-8

☒ Further documents are listed in the continuation of Box C.

☒ See patent family annex.

- |  |   |
|--|---|
| <p>* Special categories of cited documents:</p> <p>"A" document defining the general state of the art which is not considered to be of particular relevance</p> <p>"E" earlier document but published on or after the international filing date</p> <p>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>"O" document referring to an oral disclosure, use, exhibition or other means</p> <p>"P" document published prior to the international filing date but later than the priority date claimed</p> | <p>"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone</p> <p>"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art</p> <p>"&amp;" document member of the same patent family</p> |
|--|---|

Date of the actual completion of the international search

Date of mailing of the international search report

27 March 2000

20. 04. 2000

Name and mailing address of the International Searching Authority  
European Patent Office P.B. 5818 Patentlaan 2  
NL-2280 HV Rijswijk  
Tel(+31-70)340-2040, Tx 31 651 epo nl,  
Fax(+31-70)340-3016

Authorized officer

Rune Bengtsson/mj  
Telephone No.

Facsimile No.

# INTERNATIONAL SEARCH REPORT

International application No.

PCT/FI 99/01010

## C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
P,A	<p>WO 9930524 A2 (TELEFONAKTIEBOLAGET LM ERICSSON (PUBL)), 17 June 1999 (17.06.99), see the whole document</p> <p style="text-align: center;">-- -----</p>	1-8



**INTERNATIONAL SEARCH REPORT**  
Information on patent family members

International application No.  
**PCT/FI 99/01010**

Patent document cited in search report			Publication date	Patent family member(s)		Publication date
EP	0779760	A1	18/06/97	FI	101670 B	00/00/00
				FI	956036 A	16/06/97
-----						
WO	9715161	A1	24/04/97	AU	7299196 A	07/05/97
				CA	2234655 A	24/04/97
				EP	0856233 A	05/08/98
-----						
EP	0957651	A2	17/11/99	AU	9194698 A	12/04/99
				SE	9801635 D	00/00/00
-----						
WO	9930524	A2	17/06/99	AU	1896599 A	28/06/99
				NO	975783 A	10/06/99
-----						